



K4522 CC 2800-1 - S/N 62386 SSL 84m, Runner, Hook blocks 600t, 125t & 50t Year of built 2012

Carrier		
	Track 8,4m Crawler pads 1,5m Single drive Central ballast 60t 2x Central greasing pump for crawlers Hydraulic jacks for unloading Hydraulic pinning of crawlers	6x 10t
Body		
	Engine Mercedes OM 502 LA 390 kW / 530 hp Counterweight 160t + 20t H1 28mm, 158kN, 900m, 2160N/mm ² H2 28mm, 158kN, 900m, 2160N/mm ² W1/H3 28mm, 158kN, 800m, 2160N/mm ² W2 28mm, 158kN, 865m, 1960N/mm ² E 2x 30mm, 177kN, 2x 275m, 1960N/mm ² 3x Swivel (for all hoist ropes) Reeving winch 10mm, 320m, 1770N/mm ² 1x Slewing gear Hydraulic pinning Ha-Root Hydraulic pinning of Inserts Hydraulic A-frame turn over Comfort tilting cab with Airco-system Independant heating system 24V-system	10x 10t + 8 x 7,5t steel box
Main Boom		Ha 84m
	Ha-Root 10,5m, 2724-22-12 c/w W1 as H3 Ha-Insert 12m, 2724-20-11 Ha-Insert 6m, 2724-20-11 (WU 2x 3m) Ha-Insert 6m, 2724-17-11 Ha-Insert 12m, 2724-17-12 (M.P.S.) Ha-Insert 12m, 2724-14-11 Ha-Insert 12m, 2724-14-11 Ha-Reducer 12m, 2724/2421 Ha-Head 1,5m c/w Sheave Set 600t	
SL-Mast		SL 30m
	SL-Root 5,5m + W2 + SL-Head 6,5m SL-Insert 6m, 2421-10-13 SL-Insert 12m, 2421-10-12	
SL-Tray		
	Floating Tray, capacity 300t (11m / 13m / 15m)	Without counterweights
Runner		
	Runner 60t, 2m	



K4552 CC 2800-1 - S/N 62386 SSL 84m, Runner, Hook blocks 600t, 125t & 50t Year of built 2012

Hook blocks		
	Double hook block 600t, 2x 11 sheaves Single hook block 108t/125t, 3 sheaves Single hook block 47t/50t, single sheave	
LMI		
	IC 1 Full programming incl. luffer, LFVL	
Serie		
	Ground bearing pressure indication Camera surveillance winches + rear view Working area limitation Emergency control (wire-less) Emergency break-in hydraulics (man basket) Spark Arrestor in Exhaust	
Options		
	Preparation for luffer (W1 winch as H3) Preparation for ballast carrier and Tele-SL Hydraulic cylinder for crawler self-assembly 4 No. Lifting lugs on SL-tray 4-Leg chains + accessories for crawler self-assembly Supports for pin-pusher on Ha / SL-Inserts Pin-pusher Emergency stop + shutdown valve in air intake Extra 1000l tank in carbody Stacking supports on Ha- / SL-Inserts Lashing lugs on Ha- / SL-Inserts Protection plate for crawler drives Transport supports on Ha-head Fall arrest system on main boom and SL-mast	without WU-pendants without power pack
Paint		
	Daffodil yellow RAL 1007 Azure blue RAL 5009	Boom parts, Crawlers, Carbody Superstructure, A-frame, Counterweights