

K2501 LR 1600/2 - SN° 074510 HSL2DB 138m / HSL4DFB 138m+12m 2008	
---	--

Carrier		
	Track 8,4m Crawler pads 1,5m Quattro drive Central counterweight 65t - cast iron Hydraulic jacks for unloading Hydraulic pinning of crawlers 2x Central greasing pump for crawlers	2x 2,5t + 8x 7,5t
Body		
	Engine Liebherr 372kW / 505 PS Counterweight 190t - cast iron W1 28mm, 180kN, 1050m, 2160N/mm² W2 28mm, 180kN, 1050m, 2160N/mm² W3 28mm W4 28mm Reeving winch 3x Slewing gear Hydraulic pinning Ha-Root Hydraulic pinning of inserts Hydraulic A-frame turn over Comfort tilting cab with Airco-system Independant heating system Radio/ CD-player 24V-system	2x 5t + 16x 7,5t + 6x 10t
Boom	HSL2 / HSL4 138m	
	S-Root 10m, 2825.25 S-Insert 12m, 2825.45 S-Insert 12m, 2825.25 S-Insert 12m, 2825.25 S-Insert 12m, 2825.25 S-Insert 6m, 2825.20 S-Insert 12m, 2825.20 S-Insert 12m, 2825.16Z SL-Reducer 6,75m LI-Insert 12m, 2420.12 LI-Insert 6m, 2420.10 LI-Insert 12m, 2420.10Z LI-Insert 12m, 2420.9 S/W-Head 1,25m c/w Sheave Set 320t F-Adapter head 1,25m	Mid point suspenson incl. ropes: L 3525mm L 4525mm L 5525mm L 6525mm
Fixed jib	F 12m	
	F-Root 5m + Back mast F-Head 7m	Incl. backstay pendants
Derrick	D 36m	
	D-Root 9m + W3 + Bridle D-Insert 6m D-Insert 12m D-Head 9m	

K2501 LR 1600/2 - SN° 074510 HSL2DB 138m / HSL4DFB 138m+12m 2008	
---	--

Tray	Capacity 350t	
	Floating Tray, 350t capacity Continuously variable 10m-18m	without counterweights
Hook Block	SWL 200t	
	Single hook block 200t, 5 sheaves	HH-200R-002
LMI	Liccon	
	Fully programed including W, F and H	
Options		
	Jack-up rams for crawler assembly Hydr. cylinder for self-assembly + tackle Transport optimized counterweights Spark Arrestor in Exhaust Pin-pushers Emergency stop + shutdown valve in air intake Refinery label on crane Fall protection lines Stacking supports Low temeprature package H-Upgrade	without power pack
Paint		
	Daffodil yellow RAL 1007 Azure blue RAL 5009	Boom parts, Crawlers, Carbody Superstructure, A-frame, Counterweights